

GLASVEZELVERSTERKTE PROFIELEN

Profielen (mm)	Isoftaal		Vinyl -ester	Gewicht kg/m'	Oppervlak mm ²	Traagheidsmoment		Torsie constante 10 ³ mm ⁴ J
	grijs	geel				10 ³ mm ⁴ Ixx	10 ³ mm ⁴ Iyy	
Hoekprofielen								
40 x 40 x 5	x			0,66	375	56	56	
50 x 50 x 5	x			0,89	475	113	113	4
60 x 60 x 8	x			1,63	896	297	297	19,1
100 x 100 x 8	x			2,76	1536	1480	1480	32,7
U profielen								
70 x 30 x 5	x			1,08	600	408	46	5
100 x 50 x 6	x			2,04	1128	1670	263	13,5
120 x 60 x 8	x		x	3,23	1792	3770	594	38,2
150 x 50 x 6	x			2,57	1428	4430	296	17,1
200 x 80 x 8	x		x	5,15	2752	16000	1580	58,7
Kokerprofielen								
44 x 44 x 6	x			1,64	912	225	225	329
51 x 51 x 3,25	x	x		1,1	611	234	234	348
60 x 60 x 4,5	x	x	x	1,86	999	516	516	769
64 x 25 x 2 x 4	x			0,76	424	238	40	106
70 x 38 x 3	x			1,10	612	387	145	323
75 x 75 x 6	x			2,98	1656	1320	1320	1970
80 x 43 x 4 x 6	x			1,98	1060	918	287	666
120 x 30 x 3	x			1,55	864	1356	138	415
152 x 90 x 6,3 x 8	x			5,73	3167	10143	3999	8758
I en H profielen								
150 x 75 x 6	x			3,11	1728	5980	424	20,7
150 x 150 x 10	x			7,34	4236	16964	5542	131
Leuningprofielen								
Handrail	x	x	x	1,31	728	163	504	3,4
Knierail 38/32	x	x	x	0,59	330	51	51	101
Schoprand 150 mm	x	x	x	1,14	605	1110	14	1,8
Septer 60 x 60	x	x	x	1,86	999	516	516	769